

K328i DLR




THE GAME-CHANGER



3,5-28x50i with DLR-elevation turret including EasyRead lettering

The groundbreaking K328i sets new performance standards with a pioneering new-generation optical design. It offers a 40 % wider field of view*, an exceptionally comfortable eyepiece and 8x zoom with perfect optical performance across the entire adjustment range.

With DLR elevation turret optimised specially for dynamic long-range competitions with an emphasis on speed.



PRODUCT HIGHLIGHTS

- ◆ Revolutionary optical design with a 40 % wider field of view* and an exceptional eyepiece
- ◆ 8x zoom with perfect optical performance across the entire adjustment range
- ◆ Windage adjustment on the left or right, patented parallax adjustment integrated in the elevation turret
- ◆ 100 clicks per rotation – absolutely reliable repeat accuracy and clearly defined clicks
- ◆ Extra-large turret lettering for easy and fast reading
- ◆ Precise illuminated reticles in 1st focal plane

*) Based on comparison with the K525i at 25x magnification.

K328i DLR



K A H L E S

TECHNICAL DATA

K328i DLR	3,5-28x50i
Magnification	3,5 - 28
Objective lens diameter (mm)	50
Field of view (m/100m)	14,3 - 1,8
Exit pupil diameter (mm)	1,8 - 7,4
Eye relief (mm)	92
Diopter compensation (dpt.)	+2 / -3
Parallax adjustment (m)	20 - ∞
Windage	left / right
Adjustment direction	CCW
Adjustment range E/W (m/100m)	3,4 / 1,3
DLR-elevation turret incl. EasyRead	✓
Impact correction per click	.1 MRAD
Tube diameter (mm)	36
Focal plane	1.
Reticles	SKMR+, SKMR4+
Illuminated	✓
Twilight factor (DIN 58388)	13,2 - 37,4
Zero Stop	✓
TWIST GUARD	✓
Waterproof	✓
Length (mm)	360
Weight (g)	1040
Battery type	CR2032
Warranty (years)	10 (2 electronics)
Objective filter thread	M52 x 0,75
Accessories (optional)	Flip Up Cover objective/ocular, Parallax Spinner, Sunshield, Killflash ARD